



KAR LIFT SOLUTIONS
by OMER®



MODEL	VEGA 120/26	VEGA 120/26	VEGA 180/40	VEGA 240/50	VEGA 240/50	VEGA 240/50	VEGA 240/50	VEGA 240/50	
LENGTH OF PLATFORM	23' (7000 mm)	26' (8000 mm)	28' (8500 mm)	26' (8000 mm)	28' (8500 mm)	32' (9750 mm)	35' (10600 mm)	48' (14600 mm)	
LOAD CAPACITY	26,000 lbs (12000 Kg)	26,000 lbs (12000 Kg)	30,000 lbs (18000 Kg)	30,000 lbs (24000 Kg)	30,000 lbs (24000 Kg)	30,000 lbs (24000 Kg)	30,000 lbs (24000 Kg)	30,000 lbs (24000 Kg)	
LENGTH OVERALL*	30'-8" (9340mm)	33'-8" (10340mm)	35'-8" (10840mm)	34'-6" (10560mm)	35'-8" (10840mm)	40'-6" (12330mm)	43'-6" (13180mm)	56'-6" (17180mm)	
WIDTH OF PLATFORM	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	29,5" (750mm)	
WIDTH OVERALL	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	100,3" (2550mm)	
DISTANCE BETWEEN LEGS	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	41,3" (1050mm)	
HEIGHT RETRACTED	12,2" (311mm)	12,2" (311mm)	12,2" (311mm)	13,6" (343mm)	13,6" (343mm)	13,6" (343mm)	13,6" (343mm)	13,6" (343mm)	
MAX HEIGHT VER.1: ABOVE GROUND	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	73 " (1850mm)	
FLUSH MOUNT (from floor)	60,6" (1539mm)	60,6" (1539mm)	60,6" (1539mm)	59,4" (1507mm)	59,4" (1507mm)	59,4" (1507mm)	59,4" (1507mm)	59,4" (1507mm)	
MAX HEIGHT VER.2: ABOVE GROUND	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	77 " (1970mm)	
FLUSH MOUNT (from floor)	64,6" (1655mm)	64,6" (1655mm)	64,6" (1655mm)	63,4" (1625mm)	63,4" (1625mm)	63,4" (1625mm)	63,4" (1625mm)	63,4" (1625mm)	
ELECTRIC VOLTAGE	08V -24A- 60 Hz- 3P 230V- 21,7A -60Hz -3P 460V- 10,9A- 60Hz- 3P	08V -24A- 60 Hz- 3P 30V- 21,7A -60Hz -3P 60V- 10,9A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 46,5A- 60 Hz -3P 30 V- 42A- 60Hz- 3P 60V- 21A- 60Hz- 3P	08V- 62A- 60 Hz -3P 30 V- 56A- 60Hz -3P 60V- 28A- 60Hz -3P
MOTOR POWER	7,5 HP- 5,5 Kw	7,5 HP- 5,5 Kw	15 HP-11Kw	15 HP-11Kw	15 HP-11Kw	15 HP-11Kw	15 HP-11Kw	20 HP-15Kw	
NUMBER OF LEGS	4	4	6	6	6	6	6	6	
MIN. FLOOR THICK	6"	6"	6"	6"	6"	6"	6"	6"	
QUANTITY OF OIL	14,3 Gallons	14,3 Gallons	14,3 Gallons	14,3 Gallons	14,3 Gallons	14,3 Gallons	14,3 Gallons	19 Gallons	
LIFTING TIME	50 sec	50 sec	50 sec	50 sec	50 sec	50 sec	50 sec	50 sec	
WEIGHT /CB: CONT	8,725 lbs (3970 Kg)	9,275 lbs (4216 Kg)	10,670 lbs (4850 Kg)	12,760 lbs (5800 Kg)	13,000 lbs (5910 Kg)	14,100 lbs (6410 Kg)	15,620 lbs (7100 Kg)	19,400 lbs (8820 Kg)	
WEIGHT/OF : OPEN	8,660 lbs (3936Kg)	9,210 lbs (4186Kg)	10,450 lbs (4750Kg)	12,320 lbs (5600Kg)	12,560 lbs (5710Kg)	13640 lbs (6200Kg)	15,200 lbs (6910Kg)	18,900 lbs (8590Kg)	

* only version drive on-back off